

# Heat Transfer Vinyl -- Silicone PU

## SPECIFICATIONS

Composition	Thickness	Adhesive	Certifications
Silicone PU	50um and 100um	YES	

## APPLICATION INSTRUCTIONS

Applies on	SUGGESTED CUTTING SETTINGS			TRANSFER SETTINGS			
Nylon,polyester, treated fabrics,leather	Blade	Pressure	Speed	Time	Temperature	Pressure	Peel
	60°	210-270gf	200-300mm/sec	20s	160°C	Medium	Hot

### TRANSFER PROCESS :

- Mirror cut the design
- Weed excess material
- Place the design on the garment
- Heat apply at the conditions shown above
- Peel carrier hot

### PRODUCT HIGHLIGHTS :

- Applicable on different fabrics (nylon, TNT, leather)Wide range of colors

**NOTE:** We highly recommend to perform a test before launching a production

## CARE AND WASHING RECOMMENDATIONS

Washing	Ironing	Tumble dry	Dry cleaning	Storage Shelf Life	Storage Temperature	Storage Conditions	Position
Uo to 40°C, inside-out	No	Yes (synthetic cycle)	Yes	1-2 year	Between 18°C and 26°C	Away from sunlight and dust	Roll:Vertical Sheet:Level

- Wait 24 hours after the application before the first wash
- Respect the textile recommendations
- Do not bleach or use aggressive chemical agents

This document can be subject to variations. Updated versions are available on [www.visionsub.com](http://www.visionsub.com). For further information, please contact our sales office: [info@visionsub.com](mailto:info@visionsub.com)

Shanghai Vision Digital Printing Co.,Ltd  
Address  
C211 ,Building 100,No.2891, Qilianshan  
Nan Rd Pu Tuo District,Shanghai China

Contact  
Mobile: +86-18001836806  
Hotline: 021-64950449  
E-mail: [info@visionsub.com](mailto:info@visionsub.com)

